

# PowerCharge™

PowerChargeEV.com

Charge Up!

## FlexPower™ Charging Station

LEVEL 1 & 2

The PowerCharge™  
FlexPower™ is a  
dual voltage  
(120V & 240V)  
Charging Station  
Designed to  
Charge All Types of  
Electric Vehicles



PowerCharge™

**Easy-To-Use. Plug-and-Play.**

- **Simple Plug-and-Play Solution** foregoes the need to download apps, manage notifications, or push extra buttons
- **Slim, lightweight, and compact** design allows you to take it with you for fast on-the-go charging or hang on wall with included bracket
- **Travel** case included

**Quick Access**

- **Quickly access high power** charging at up to 7.7kW, faster than a standard Level 1 charging station
- **Add up to 30 miles** range per hour charged, depending on your vehicle's efficiency

**Intelligent Grid Plug**

- **Swappable grid** plug enables low and high power charging
- **Designed with** thermal detection, auto-restart and recovery, and ground detection against defaults
- **Smart Plug** Technology automatically determines and sets the correct power level according to global technical and legal requirements
- **Included adapters** (120V & 240V) allows you to choose the right power for your charging application

**Status Light**

- **3 LED** light status bar

**Charging Cable**

- **20 ft.** charging cable length

**Charging Connector**

- **J1772 Plug Type** which is applicable for all vehicles meeting US standards

**Safe & Reliable**

- **NEMA 6P Watertight** rating protects this charger if submerged in up to 3 ft. of water
- **Safely charge indoors** or outdoors, no matter the weather conditions
- **Easily mount in your** garage with included bracket
- **UL and cUL Certified**



CONFIGURATION	PC-FLEXPOWER-DV
Max Current	240V @ 32A (7.7kW); 120V @ 12A (1.4kW)
System package	12.6 in x 12.6 in x 3.94 in (320 x 320 x 100 mm)
AC Compatibility	85 - 265 VAC, 45 - 65 Hz
Plug Type	NEMA 14-50 and IEC types
Cable Length	20 ft (6m)
Weight	9 lbs (4.1 kg) - module
Operating Temperature	-40C (-40°F) to +75C (167°F)
Indoor / Outdoor	Yes   NEMA 6P watertight, IP67 (up to 3ft submerged)
Certified Altitude	13,123 ft (4000m)
Vehicle Connector	SAE, IEC
Certification	UL, cUL
HMI	3 LED status bar
Warranty	Limited 2-Year

